## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

# SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 1.1. Product identifier Product name : MINT ZONE / MENTHE 160ML Product code : P01329V01/02. 1.2. Relevant identified uses of the substance or mixture and uses advised against atmosphere desodorizer 1.3. Details of the supplier of the safety data sheet Registered company name : PRODIFA. Address : ZAE LES DIX MUIDS - 59770 - MARLY - FRANCE. Telephone : 03.27.28.19.19 Fax : 03.27.28.19.10 info@prodifa.com http://www.prodifa.com/ 1.4. Emergency telephone number : +33 (0)1.45.42.59.59. Association/Organisation : INRS/ORFILA http://www.centres-antipoison.net. **SECTION 2 : HAZARDS IDENTIFICATION** 2.1. Classification of the substance or mixture In compliance with EC regulation No. 1272/2008 and its amendments. Flammable aerosol, Category 1 (Aerosol 1, H222 - H229). Eye irritation, Category 2 (Eye Irrit. 2, H319). Skin sensitisation, Category 1 (Skin Sens. 1, H317). This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use. In compliance with directives 67/548/EEC, 1999/45/EC and their amendments. Extremely flammable (F+, R 12). Skin sensitisation (Xi, R 43). This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site. This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use. 2.2. Label elements Mixture for spray application. Mixture for aerosol application. In compliance with EC regulation No. 1272/2008 and its amendments. Hazard pictograms : GHS07 GHS02 Signal Word : DANGER Product identifiers : CARVONE EC 202-759-5 Hazard statements : H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Precautionary statements - General :				
P101	If medical advice is needed, have product container or label at hand.			
P102	Keep out of reach of children.			
Precautionary statements - Prevention :				
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.			
P211	Do not spray on an open flame or other ignition source.			
P251	Do not pierce or burn, even after use.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
Precautionary statements - Storage :				
P410 + P412	Protect from sunlight. Do no expose to temperatures exceeding 50 oC/122oF.			
Precautionary statements - Disposal :				
P501	Eliminate the contents / container according to the local regulations.			
2.3. Other hazards				

#### MINT ZONE / MENTHE 160ML

The mixture does not contain any substances classified as 'Substances of Very High Concern' (SVHC) by the European CHemical s Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

#### **Composition :**

Identification	(EC) 1272/2008	67/548/EEC	Note	%
INDEX: 601_004_00_0	GHS02, GHS04	F+	C [1]	25 <= x % < 50
CAS: 106-97-8	Dgr	F+;R12		
EC: 203-448-7	Flam. Gas 1, H220			
REACH: 01-2119474691-32				
BUTANE				
INDEX: 603_002_005A	GHS07, GHS02	F	[1]	10 <= x % < 25
CAS: 64-17-5	Dgr	F;R11		
EC: 200-578-6	Flam. Liq. 2, H225			
REACH: 01-2119457610-43	Eye Irrit. 2, H319			
ETHANOL				
INDEX: 603-117-00-0	GHS02, GHS07	Xi,F	[1]	2.5 <= x % < 10
CAS: 67-63-0	Dgr	Xi;R36		
EC: 200-661-7	Flam. Liq. 2, H225	F;R11		
REACH: 01-2119457558-25	Eye Irrit. 2, H319	R67		
	STOT SE 3, H336			
PROPAN-2-OL				
INDEX: I1490_04_6	GHS07	Xi		1 <= x % < 2.5
CAS: 1490-04-6	Wng	Xi;R38		
EC: 216-074-4	Eye Irrit. 2, H319			
MENTHOL	Skin Irrit. 2, H315			
	CHE07	v		1 . 0/ . 25
INDEX: 199_49_0	GHS07	Xn X		1 <= x % < 2.5
CAS: 99-49-0	Wng	Xn;R22		
EC: 202-759-5	Acute Tox. 4, H302	Xi;R43		
CARVONE	Skin Sens. 1B, H317			
INDEX: B4180238	GHS09, GHS07	Xi,N		0 <= x % < 1
CAS: 4180-23-8	Wng	Xi;R43		
EC: 224-052-0	Skin Sens. 1, H317	N;R51/53		
	Aquatic Chronic 2, H411	.,		

#### MINT ZONE / MENTHE 160ML

(E)-ANETHOLE			
INDEX: 601-029-00-7	GHS02, GHS07, GHS09	Xi,N	$0 \le x \% < 1$
CAS: 5989-27-5	Wng	Xi;R38-R43	
EC: 227-813-5	Flam. Liq. 3, H226	N;R50/53	
	Skin Irrit. 2, H315	R10	
(R)-P-MENTHA-1,8-DIENE	Skin Sens. 1, H317		
	Aquatic Acute 1, H400		
	M Acute $= 1$		
	Aquatic Chronic 1, H410		
	M Chronic $= 1$		

### Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

#### **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

#### 4.1. Description of first aid measures

#### In the event of exposure by inhalation :

Move the patient to free air at rest.

#### In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

#### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

#### In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed** No data available.

### **SECTION 5 : FIREFIGHTING MEASURES**

#### Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

## 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

- water with AFFF (Aqueous Film Forming Foam) additive

### MINT ZONE / MENTHE 160ML

- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

#### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

#### 5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

### SECTION 6 : ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Prevent every risk of ignition of the steams.

Eliminate the fire in the zone.

The pouring can bring the surfaces slippery.

#### For non fire-fighters

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area. Avoid any contact with the skin and eyes.

#### For fire-fighters

Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

#### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

Use some absorbent.

The elimination must be carried out by a registrated salvage professionnal.

## 6.4. Reference to other sections

No data available.

#### SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Prevent every contact with the skin and the eyes.

Pulverise by short pressions, without prolonged pulverisation.

Follow hygiene and security rules because flamable capacity.

#### MINT ZONE / MENTHE 160ML

## Do not inhale steams.

Do not smoke.

Handle and store away from ignition sources and reductive substances

## Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

## Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Do not smoke.

Gloves and glasses are recommanded.

Keep the original packing. Do not pierce or burn even after use.

Follow the hygiene and security rules.

Rules of storage and manipulation applicables to the gaz under pressure.

Use only in well-ventilated premises.

### Prohibited equipment and procedures :

## No smoking, eating or drinking in areas where the mixture is used.

#### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

## Packaging

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

### SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

**Occupational exposure limits :** - France (INRS - ED984 :2008) :

- Mance (INKS - ED9	.2008).					
CAS	VME-ppm :	VME-mg/m	3 : VLE-ppm :	VLE-mg/m3:	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-
64-17-5	1000	1900	5000	9500	-	84
67-63-0	-	-	400	980	-	84
- UK / WEL (Workpla	ace exposure limi	its, EH40/2005,	, 2007) :			
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
106-97-8	600 ppm	750 ppm	-	-	-	
64-17-5	1000 ppm	-	-	-	-	
67-63-0	400 ppm	500 ppm	-	-	-	

### 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of spraying, wear protective clothing against chemical risks and against sprayed liquid (type 4) in accordance with EN14605 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed. Wash with soaped watter, then rinse with watter during 15min in case of contact.

### - Respiratory protection

Prevent any inhalation from the fog.

#### SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES 9.1. Information on basic physical and chemical properties **General information :** Fluid liquid. Physical state : Spray. Important health, safety and environmental information pH: Not relevant. 82 °C. Boiling point/boiling range : Vapour pressure $(50^{\circ}C)$ : Not relevant. Density : < 1 Water solubility : Dilutable. v < 7 mm2/s (40°C) Viscosity: Melting point/melting range : Not specified. 200 °C. Self-ignition temperature : Decomposition point/decomposition range : 200 °C. Chemical combustion heat : >= 30 kJ/g.9.2. Other information No data available.

## SECTION 10 : STABILITY AND REACTIVITY

**10.1. Reactivity** No data available.

## 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### **10.4.** Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises. Avoid :

- heating
- heat
- accumulation of electrostatic charges.
- flames and hot surfaces

#### **10.5. Incompatible materials**

- Keep away from :
- strong oxidising agents

### 10.6. Hazardous decomposition products The

- thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)

### SECTION 11 : TOXICOLOGICAL INFORMATION

A big inhalation can be the cause of waves of nausea and of irritation of the respiratory mucous membranes.

Accidentally ingestion cause burn of the throat, which can be accompanied by gastric pain.

Frequents contacts or prolonged ones can cause irritations.

Dry out action of the skin.

Rinse immediately. If feelings of irritation appear, consult a doctor.

### 11.1. Information on toxicological effects

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage May cause an allergic reaction by skin contact. **11.1.1**. **Substances** 

Substances	
Acute toxicity :	
CARVONE (CAS: 99-49-0)	
Oral route :	LD50 = 1600  mg/kg
Dermal route :	LD50 = 3800  mg/kg
MENTHOL (CAS: 1490-04-6)	
Oral route :	LD50 = 2600  mg/kg
Serious damage to eyes/eye irritation :	
ETHANOL (CAS: 64-17-5)	
Causes serious eye irritation.	
Corneal haze :	$1 \le$ Average score $< 2$ and effects totally reversible within 21 days of observation
Conjunctival redness :	$2 \le$ Average score < 2.5 and effects totally reversible within 21 days of observation
11.1.2. Mixture	
Other information	
Ethanol INRS N°48	
Monograph(s) from the IARC (International Age	•
CAS 64-17-5 : IARC Group 1 : The agent is carcin	
CAS 67-63-0 : IARC Group 3 : The agent is not cl	lassifiable as to its carcinogenicity to humans.
CAS 5989-27-5 : IARC Group 3 : The agent is not	t classifiable as to its carcinogenicity to humans.
SECTION 12 : ECOLOGICAL INFORMATION	
12.1. Toxicity	
12.1.2. Mixtures	
No aquatic toxicity data available for the mixture.	
12.2. Persistence and degradability	
No data available.	
12.3. Bioaccumulative potential	
No data available.	
12.4. Mobility in soil	
No data available.	
12.5. Results of PBT and vPvB assessment	
No data available.	

#### 12.6. Other adverse effects

Do not throw out product in the nature, in residual watters or superficials ones

### SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC. Aerosol do not pierce or burn after use

CONSIGN TO AN APPROVED COLLECTOR. CONSULT THE PREFECTORAL ORDERS IN FORCE.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company. Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

### Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

## SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2013).

#### 14.1. UN number

1950

### 14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

### **14.3.** Transport hazard class(es)

- Classification :



2.1

#### 14.4. Packing group

-

## 14.5. Environmental hazards

.

#### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ		1	
	2.1	See SP63	-	SP277	F-D,S-U	63 190 277 327 344 959	EO			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A145 A167 A802	E0	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

## SECTION 15 : REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:
- The following regulations have been used:
- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- Directive 75/734/CEE modified by directive 2013/10/UE

#### MINT ZONE / MENTHE 160ML

- Regulation EC 1272/2008 modified by regulation EC 618/2012
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.

- Container information: No data available.

- Particular provisions :

No data available.

#### 15.2. Chemical safety assessment

No data available.

### **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

## Hazard symbols :

Irritant

~



Extremely flammable

Contains :		
EC 202-759-5	CARVONE	
Risk phrase :		
R 43		May cause sensitisation by skin contact.
R 12 Extremely flamma	able.	
Safety phrase :		
		Keep away every burn, ignition source or spark - do not smoke.
S 2 Keep out of the re	each of children.	
S 23		Do not breathe the vapours.
S 24		Avoid contact with skin.
S 37		Wear suitable gloves.
S 46 If swallowed, seel from sunlight and do no		immediately and show this container or label. Pressurized container: protect eratures
e	1 1	exceeding 50°C.
		Do not pierce or burn, even after use.
		Do not spray on a naked flame or any incandescent material.
S 51		Use only in well-ventilated areas.
		Pulverise by short pressions, without prolonged pulverisation.
		Do not use for any purpose other than the one for which it is intended.
Fitle for H, EUH and R	indications men	tioned in section 3 :
H220		Extremely flammable gas.
H225		Highly flammable liquid and vapour.
H226		Flammable liquid and vapour.
H280		Contains gas under pressure; may explode if heated.
H302		Harmful if swallowed.
H315		Causes skin irritation.
H317		May cause an allergic skin reaction.

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
R 10	Flammable.
R 11	Highly flammable.
R 12	Extremely flammable.
R 22	Harmful if swallowed.
R 36	Irritating to eyes.
R 38	Irritating to skin.
R 43	May cause sensitisation by skin contact.
R 50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 67	Vapours may cause drowsiness and dizziness.
Abbreviations :	

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark